

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 13565752
Catalog # : 00718EP3EHP213TYZ7F3

| | | | |
|-----------------------|--------------------|-----------------------------|------------------------|
| Frame | : 213TYZ | Locked rotor time | : 25s (cold) 14s (hot) |
| Output | : 7.5 HP (5.5 kW) | Temperature rise | : 80 K |
| Poles | : 4 | Duty cycle | : S3 |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C |
| Rated voltage | : 208-230/460 V | Altitude | : 1000 m.a.s.l. |
| Rated current | : 24.0-21.7/10.9 A | Protection degree | : IP55 |
| L. R. Amperes | : 209-189/94.8 A | Cooling method | : IC411 - TEFC |
| LRC | : 8.7x(Code M) | Mounting | : F-3 |
| No load current | : 16.8-15.2/7.60 A | Rotation ¹ | : Both (CW and CCW) |
| Rated speed | : 1775 rpm | Noise level ² | : 58.0 dB(A) |
| Slip | : 1.39 % | Starting method | : Direct On Line |
| Rated torque | : 21.9 ft.lb | Approx. weight ³ | : 0.0 lb |
| Locked rotor torque | : 290 % | | |
| Breakdown torque | : 409 % | | |
| Insulation class | : F | | |
| Service factor | : 1.15 | | |
| Moment of inertia (J) | : A | | |
| Design | | | |

| | | | | | |
|----------------|------|------|------|------|------------------|
| Output | 25% | 50% | 75% | 100% | Foundation loads |
| Efficiency (%) | 82.0 | 84.0 | 87.5 | 89.5 | Max. traction |
| Power Factor | 0.27 | 0.48 | 0.62 | 0.71 | Max. compression |

| | | Drive end | Non drive end |
|----------------------|---|------------------|---------------|
| Bearing type | : | 6308 ZZ | 6207 ZZ |
| Sealing | : | V'Ring | V'Ring |
| Lubrication interval | : | - | - |
| Lubricant amount | : | - | - |
| Lubricant type | : | Mobil Polyrex EM | |

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|------------------------|---------|------|
| | | | | |
| Performed by | | Page Revision 1 / 1 | | |
| Checked by | | | | |
| Date | 23/01/2018 | | | |