DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:



Customer

				Product code :	t code : 12147877			
		Three-Phase		(Catalog # :	03089EP30	QCT324V-W22	
Frame		: 324T		Cooling	method	: IC411 - TE	FC	
Insulation class		: F	Mounting			: F-2		
Duty cycle		: Cont.(S1)				: Both (CW and CCW)		
Ambient temperature		: -20°C to +40°C			method	: Direct On Line		
Altitude		: 1000 m.a.s.l.	000 m.a.s.l. Approx. weight ³			: 539 lb		
Protection degree		: IP55			of inertia (J)			
Output [HP]		30				7.5		
Poles		4			8			
Frequency [Hz]		60			60			
Rated voltage [V]		460			460			
Rated current [A]			37.2		14.2			
L. R. Amperes [A]		301			51.0			
.RC [A]		8.1x(Code J)		3.6x(Code F)				
No load current [A]	17.0				8.80		
ated speed [RPN	-	1780				885		
lip [%]		1.11				1.67		
Rated torque [ft.lb]	1	87.3				43.9		
		270				43.9		
Locked rotor torque [%] Breakdown torque [%]		270				180		
	[/0]							
Service factor		80 k	1.25			1.25		
Temperature rise						80 K		
Locked rotor time		19s (cold) 11s (hot)			90s (cold) 50s (hot)			
Noise level ²		69.0 dE	. ,			56.0 dB(A)		
	25%	89.4				81.0		
Efficiency (%)	50%	90.2			82.5			
	75%		91.0			84.0		
	100%	91.7	91.7			85.5		
	25%	0.39	9		0.22			
Power Factor	50%	0.64	1	0.38				
	75%	0.75	5		0.50			
	100%	0.81	1			0.57		
	1	Drive end Non driv	e end F	Foundatio	on loads			
Bearing type		: 6312 62		Max. traction : 17 lb				
Bearing type		2RS C3 2RS		Max. II au		. 17 10		
Sealing		: V'Ring V'R		Max. compression : 555 lb				
Lubrication interv	/al	·			ipreceient			
Lubricant amount			- Mobil Polyrox EM					
Lubricant type			//	Mobil Polyrex EM				
Notes								
Notes								
This revision repla must be eliminate (1) Looking the m (2) Measured at 1	ed. otor from the m and with t veight subjec ocess.	icel the previous one, whice shaft end. olerance of +3dB(A). t to changes after	þ			based on tests w ne tolerances stipu		
This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro	ed. otor from the m and with t veight subjec ocess.	shaft end. olerance of +3dB(A). t to changes after	þ	power su				
This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful	ed. otor from the m and with t veight subjec ocess.	shaft end. olerance of +3dB(A).	þ	power su	pply, subject to th	ne tolerances stipu	lated in NEMA	
This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful	ed. otor from the m and with t veight subjec ocess.	shaft end. olerance of +3dB(A). t to changes after	þ	power su	pply, subject to th	ne tolerances stipu	lated in NEMA	
This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful Rev. Performed by	ed. otor from the m and with t veight subjec ocess.	shaft end. olerance of +3dB(A). t to changes after	þ	power su	pply, subject to th	ne tolerances stipu Checked	Ilated in NEMA	
This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful Rev.	ed. otor from the m and with t veight subjec ocess.	changes Summary	þ	power su	pply, subject to th	ne tolerances stipu	lated in NEMA	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A. Subject to change without notice

Three Phase Induction Motor - Squirrel Cage

Customer

:

Space heater information

Voltage: 110-127/200-240 V

Rev.		Changes Summary	Performed	Checked	Date		
Performed by							
Checked by				Page	Revision		
Date	18/01/2018			2/2			
This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.							

Subject to change without notice

