

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting IE3 Three-Phase Product code : 13984015  
Catalog # : 00218ET3WAL100L-W22

Frame : 100L	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : B3L(E)
Duty cycle : S1	Rotation <sup>1</sup> : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight <sup>3</sup> : 61.6 lb
Protection degree : IP55	Moment of inertia (J) : 0.2136 sq.ft.lb
Design : N	

Output [HP]	3	3	3	3
Poles	4	4	4	4
Frequency [Hz]	60	50	50	50
Rated voltage [V]	460	220/380	400	240/415
Rated current [A]	4.11	8.43/4.88	4.87	8.42/4.87
L. R. Amperes [A]	37.0	62.4/36.1	39.4	70.7/40.9
LRC [A]	9.0	7.4	8.1	8.4
No load current [A]	2.60	4.49/2.60	2.90	5.36/3.10
Rated speed [RPM]	1750	1435	1440	1445
Slip [%]	2.78	4.33	4.00	3.67
Rated torque [ft.lb]	8.88	10.9	10.8	10.8
Locked rotor torque [%]	380	280	370	409
Breakdown torque [%]	370	300	360	400
Service factor	1.25	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	36s (cold) 20s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)
Noise level <sup>2</sup>		53.0 dB(A)	53.0 dB(A)	53.0 dB(A)
Efficiency (%)	25%	85.2	87.2	86.2
	50%	86.6	87.2	86.5
	75%	88.2	87.1	87.0
	100%	89.5	86.7	87.0
Power Factor	25%	0.30	0.33	0.30
	50%	0.54	0.57	0.53
	75%	0.67	0.70	0.66
	100%	0.75	0.79	0.75

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6206 ZZ	6205 ZZ	Max. traction : 301 lb
Sealing :	V'Ring	V'Ring	Max. compression : 363 lb
Lubrication interval :	-	-	
Lubricant amount :	-	-	
Lubricant type :	Mobil Polyrex EM		

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/01/2018			

Page 1 / 1  
Revision