## DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:



## Customer

Frame Insulation class Duty cycle Ambient tempera Altitude Protection degree		· · · · · · · · · · · · · · · · · · ·		Catal	oa # :	00109F	T3F182T-W22	
Insulation class Duty cycle Ambient tempera Altitude			Three-Phase		Catalog # :		00109ET3E182T-W22	
Duty cycle Ambient tempera Altitude		: 182/4T		Cooling meth	od	: IC411	- TEFC	
Ambient tempera Altitude		: F		Mounting		: F-1		
Altitude		: Cont.(S1)		Rotation <sup>1</sup>		: Both (CW and CCW)		
	iture	: -20°C to +40°C		Starting meth		: Direct On Line		
Protection deare		: 1000 m.a.s.l.		Approx. weig		: 81.5 lb		
Design	e	: IP55 : B		Moment of in	ertia (J)	: 0.399	1 sq.ft.lb	
-				1	1		1	
Output [HP] Poles		1		1 8	1		<u> </u>	
Frequency [Hz]		8 60		50	8		50	
Rated voltage [V]		208-230/460		380	400		415	
Rated voltage [v] Rated current [A]		5.09-4.60/2.30		2.52	2.5		2.61	
		30.5-27.6/13.8		15.1			15.7	
L. R. Amperes [A]					15.4 6.0x(Code M)		-	
LRC [A]							6.0x(Code N)	
No load current [A]		2.93-3.40/1.70		1.67	1.82		1.94	
Rated speed [RPM]		875		715	715		720	
Slip [%]		2.78		4.67	4.6		4.00	
Rated torque [ft.lb]		5.92	L	7.25	7.2		7.20	
Locked rotor torque [%]		300		240	270		300	
Breakdown torque [%]		350		250	280		310	
Service factor		1.25	ļ	1.00	1.0		1.00	
Temperature rise		80 K		80 K	80		80 K	
Locked rotor time		39s (cold) 22s (hot)		cold) 22s (hot)	39s (cold) 2		39s (cold) 22s (hot)	
Noise level <sup>2</sup>		50.0 dB(A)	4	6.0 dB(A)	46.0 dl	B(A)	46.0 dB(A)	
Efficiency (%)	25% 50%	74.0		747	70	<u> </u>	70.0	
		74.0		74.7	72.0		70.0	
	75%	77.0		75.5	75.		74.0	
	100%	78.5		75.5	75.	D	75.5	
Power Factor	25%	0.00		0.00	0.05		0.00	
	50%	0.32	ļ	0.38	0.3		0.33	
	75%	0.42		0.50	0.4		0.43	
	100%	0.52	<u> </u>	0.60	0.5	0	0.53	
<b>D</b>			rive end	Foundation loa	ads			
Bearing type		_		Max. traction				
Sealing		: V'Ring V'	'Ring Max. compression		sion	: 185 lb		
Lubrication interval		: -	-					
Lubricant amount								
Lubricant type		: Mobil Polyrex EM						
Notes								
must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro	d. otor from the m and with t veight subjec ocess.	ncel the previous one, wh e shaft end. olerance of +3dB(A). ct to changes after	nich				ts with sinusoidal stipulated in NEMA	
(4) At 100% of ful	l load.							
Rev.		Changes Summary		P	erformed	Checked	Date	
Performed by								
Performed by Checked by					1	Page	Revision	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

Subject to change without notice