

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium  
Efficiency Three-Phase

Product code : 12674854

Catalog # : 002120T3H184TC-S

Frame : 182/4TC  
Output : 2 HP (1.5 kW)  
Poles : 6  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 2.36 A  
L. R. Amperes : 15.6 A  
LRC : 6.6x(Code J)  
No load current : 1.37 A  
Rated speed : 1165 rpm  
Slip : 2.92 %  
Rated torque : 8.89 ft.lb  
Locked rotor torque : 200 %  
Breakdown torque : 300 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.2800 sq.ft.lb  
Design : B

Locked rotor time : 59s (cold) 33s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Cooling method : IC01 - ODP  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 52.0 dB(A)  
Starting method : Direct On Line

Output	25%	50%	75%	100%
Efficiency (%)	84.4	85.5	86.5	87.5
Power Factor	0.30	0.53	0.66	0.73

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	22/01/2018				
			Page		Revision
			1 /		