DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Cooling Tower High Efficiency Product code: 12174043 Three-Phase Catalog #: 03089EP3PCT326V2F1-W Frame : 324/6T Cooling method : IC411 - TEFC Insulation class Mounting : F-1 Duty cycle : Cont.(S1) Rotation¹ : Both (CW and CCW) Ambient temperature : -20°C to +40°C Starting method : Direct On Line : 1000 m.a.s.l. Approx. weight3 : 2.2 lb Altitude : IP55 : 9.16 sq.ft.lb Protection degree Moment of inertia (J) Output [HP] 30 7.5 Poles 4 8 Frequency [Hz] 60 60 Rated voltage [V] 200 200 Rated current [A] 85.9 40.6 L. R. Amperes [A] 601 170 LRC [A] 7.0x(Code J) 4.2x(Code K) No load current [A] 32.2 27.6 Rated speed [RPM] 1780 890 Slip [%] 1.11 1.11 Rated torque [ft.lb] 87.3 43.7 Locked rotor torque [%] 220 220 Breakdown torque [%] 260 250 Service factor 1.25 1.25 Temperature rise 80 K 80 K Locked rotor time 27s (cold) 15s (hot) 30s (cold) 17s (hot) Noise level² 69.0 dB(A) 56.0 dB(A) 25% 89.4 71.3 50% 90.2 74.0 Efficiency (%) 75% 91.7 78.5 100% 92.4 81.5 25% 0.42 0.18 50% 0.30 0.65 Power Factor 75% 0.75 0.40 100% 0.80 0.48 Non drive end Foundation loads Drive end Bearing type 6312 6212 Max. traction : 417 lb 2RS C3 2RS C3 Sealing V'Ring V'Ring Max. compression : 420 lb Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date	
Performed by						
Checked by					Page	Revision
Date	18/01/2018				1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three Phase induction wotor - Squirer Cage								
Customer	:							
		Space heater informa	ntion					
Voltage: 110-127	7/200-240 V							
			T 5					
Rev.		Changes Summary	Performed	Checked	Date			
Performed by								
Checked by				Page	Revision			
Date	18/01/2018			2/2				