

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump NEMA
Premium Efficiency Three-Phase

Product code : 12676979

Catalog # : 00518OT3H184JM-S

Frame : 182/4JM
Output : 5 HP (3.7 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 5.06 A
L. R. Amperes : 36.5 A
LRC : 7.2x(Code J)
No load current : 2.52 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 14.7 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 310 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.4003 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 55.0 dB(A)
Starting method : Direct On Line

Output	25%	50%	75%	100%
Efficiency (%)	87.5	88.5	88.5	89.5
Power Factor	0.38	0.63	0.76	0.82

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	19/01/2018				
			Page	Revision	
			1 /		