DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer

Product line : W22 Tru-Metric IE3 Three-Phase Product code: 12541472

> Catalog #: 01809ET3Y225S/M-W22

Cooling method Frame : 225S/M : IC411 - TEFC

Insulation class : F Mounting : B3L(E)

Duty cycle : S1 Rotation¹ : Both (CW and CCW) : -20°C to +40°C Starting method : Direct On Line

Ambient temperature Approx. weight³ Altitude : 1000 m.a.s.l. : 831 lb Moment of inertia (J) : 26.3 sq.ft.lb

Protection degree : IP55

Design		: N	Wiement of the	. 20.0 5q.16.18			
Output [HP]		25	25	25	25		
Poles		8	8	8	8		
Frequency [Hz]		60	50	50	50		
Rated voltage [V]		460	380	400	415		
Rated current [A]		31.6	36.7	35.6	34.6		
L. R. Amperes [A]		221	239	231	225		
LRC [A]		7.0	6.5	6.5	6.5		
No load current [A]		15.9	16.8	17.0	17.9		
Rated speed [RPM]		885	730	735	735		
Slip [%]		1.67	2.67	2.00	2.00		
Rated torque [ft.lb]		146	177	176	176		
Locked rotor torque [%]		190	150	170	190		
Breakdown torque [%]		310	220	250	270		
Service factor		1.25	1.00	1.00	1.00		
Temperature rise		80 K	80 K	80 K	80 K		
Locked rotor time		77s (cold) 43s (hot)	50s (cold) 28s (hot)	50s (cold) 28s (hot)	50s (cold) 28s (hot)		
Noise level ²		60.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)		
	25%	92.9	93.5	93.1	92.7		
Efficiency (%)	50%	93.0	93.1	93.0	92.8		
Efficiency (70)	75%	93.0	92.8	93.0	93.0		
	100%	93.0	92.2	92.7	92.9		
	25%	0.35	0.40	0.38	0.35		
Power Factor	50%	0.60	0.67	0.63	0.60		
	75%	0.72	0.78	0.75	0.73		

100% 0.79 0.83 Non drive end Foundation loads Drive end

Bearing type 6314 C3 6314 C3 Max. traction : 1235 lb Sealing **WSeal** WSeal Max. compression : 2066 lb

Lubrication interval 20000 h 20000 h Lubricant amount 27 g 27 g Mobil Polyrex EM Lubricant type

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

0.81

0.80

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	22/01/2018			1/1	