

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel High Efficiency Three-Phase
Product code : 12892587
Catalog # : 02536OP3VFP256TC-S

Frame	: 254/6TC	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 25 HP (18.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 66.7/33.3 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 414/207 A	Mounting	: F-1
LRC	: 6.2x(Code G)	Rotation ¹	: Both (CW and CCW)
No load current	: 25.7/12.9 A	Noise level ²	: 70.0 dB(A)
Rated speed	: 3530 rpm	Starting method	: Direct On Line
Slip	: 1.94 %		
Rated torque	: 36.7 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.8718 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	90.0	90.2	91.0	91.0
Power Factor	0.48	0.75	0.84	0.88

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 /		
Checked by				
Date	18/01/2018			