

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Multimounting IE3 Three-Phase Product code : 13983177
Catalog # : 00436ET3EAL112M-W22

Frame : 112M	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : B3L(E)
Duty cycle : S1	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 79.6 lb
Protection degree : IP55	Moment of inertia (J) : 0.1898 sq.ft.lb
Design : N	

Output [HP]	5.5	5.5	5.5	5.5
Poles	2	2	2	2
Frequency [Hz]	60	50	50	50
Rated voltage [V]	230/460	380	400	415
Rated current [A]	13.3/6.67	7.75	7.50	7.39
L. R. Amperes [A]	115/57.4	59.7	57.7	56.9
LRC [A]	8.6	7.7	7.7	7.7
No load current [A]	4.60/2.30	2.20	2.60	2.90
Rated speed [RPM]	3505	2890	2900	2905
Slip [%]	2.64	3.67	3.33	3.17
Rated torque [ft.lb]	8.13	9.86	9.83	9.81
Locked rotor torque [%]	310	260	290	320
Breakdown torque [%]	440	310	350	380
Service factor	1.25	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	43s (cold) 24s (hot)	39s (cold) 22s (hot)	39s (cold) 22s (hot)	39s (cold) 22s (hot)
Noise level ²	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)
Efficiency (%)	25%	84.3	88.4	87.4
	50%	85.5	88.6	88.1
	75%	87.5	89.2	89.1
	100%	88.5	89.1	89.5
Power Factor	25%	0.46	0.51	0.46
	50%	0.67	0.73	0.69
	75%	0.79	0.83	0.80
	100%	0.85	0.88	0.86

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6207 ZZ	6206 ZZ	Max. traction : 202 lb
Sealing :	V'Ring	V'Ring	Max. compression : 282 lb
Lubrication interval :	-	-	
Lubricant amount :	-	-	
Lubricant type :	Mobil Polyrex EM		

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	22/01/2018			