

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium
Efficiency Three-Phase

Product code : 12682579

Catalog # : 00336OT3H145T-S

Frame : 143/5T
Output : 3 HP (2.2 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 2.87 A
L. R. Amperes : 23.0 A
LRC : 8.0x(Code J)
No load current : 1.04 A
Rated speed : 3480 rpm
Slip : 3.33 %
Rated torque : 4.47 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1279 sq.ft.lb
Design : B

Locked rotor time : 16s (cold) 9s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 62.0 dB(A)
Starting method : Direct On Line

Output	25%	50%	75%	100%
Efficiency (%)	83.7	84.0	85.5	85.5
Power Factor	0.50	0.76	0.86	0.90

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 /		
Checked by				
Date	23/01/2018			