

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 13035066  
Catalog # : 02218ET3Y180LFF-W22

Frame	: 180L	Locked rotor time	: 34s (cold) 19s (hot)
Output	: 30 HP (22 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 36.0 A	Protection degree	: IP55
L. R. Amperes	: 342 A	Cooling method	: IC411 - TEFC
LRC	: 9.5	Mounting	: B35L(E)
No load current	: 16.8 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1775 rpm	Noise level <sup>2</sup>	: 63.0 dB(A)
Slip	: 1.39 %	Starting method	: Direct On Line
Rated torque	: 12.3 kgfm	Approx. weight <sup>3</sup>	: 219 kg
Locked rotor torque	: 380 %		
Breakdown torque	: 390 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.2272 kgm <sup>2</sup>		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	89.8	91.0	92.4	93.6	Max. traction	: 652 kgf
Power Factor	0.40	0.65	0.76	0.82	Max. compression	: 871 kgf

		Drive end	Non drive end
Bearing type	:	6311 C3	6211 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	07/01/2022			
			Revision	