DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:



Customer

Product line		: W22 Cooling Tower NEMA Premium Efficiency Three-Pr			Product code :		12127098	12127098		
		FIEIII		y mee-Ph		alog # :	04018AT3P0	CT324TF1-W2		
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J) Design		: 324T : 40 HP (30 kW) : 4 : 60 Hz : 200 V : 108 A : 661 A : 661 A : 6.1x(Code G) : 36.8 A : 1775 rpm : 1.39 % : 117 ft.lb : 220 % : 240 % : F : 1.25 : 9.16 sq.ft.lb : B			Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation ¹ Noise level ² Starting method Approx. weight ³		: 80 K : Cont.(S1) : -20°C to + : 1000 m.a. : IP55 : IC410 - TE : F-1 : Both (CW : 66.0 dB(A	: Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC410 - TEAO : F-1 : Both (CW and CCW) : 66.0 dB(A) : Direct On Line		
Output	25%	50%	75%	100%	Foundation lo	oads				
Efficiency (%) Power Factor	93.5 0.47	93.6 0.72		94.1 0.85	Max. traction Max. compres		: 816 lb : 1364 lb			
Bearing type Sealing	Pal	:	V'Rii	ng		V'Ring				
Lubrication interv Lubricant amoun Lubricant type Notes			-	Mo	bil Polyrex EM	-				
Lubricant amoun Lubricant type	aces and o d. otor from m and wit veight sub ocess.	the shaft e	nd. e of +3dB(A).	, which	These are av	verage values	based on tests wi e tolerances stipu			
Lubricant amoun Lubricant type Notes This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro	aces and o d. otor from m and wit veight sub ocess.	the shaft e th toleranc ject to cha	nd. e of +3dB(A).	, which	These are av power supply MG-1.	verage values				
Lubricant amoun Lubricant type Notes This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful	aces and o d. otor from m and wit veight sub ocess.	the shaft e th toleranc ject to cha	end. e of +3dB(A). nges after	, which	These are av power supply MG-1.	verage values y, subject to th	e tolerances stipu	lated in NEMA		
Lubricant amoun Lubricant type Notes This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful Rev.	aces and o d. otor from m and wit veight sub ocess.	the shaft e th toleranc ject to cha	end. e of +3dB(A). nges after	, which	These are av power supply MG-1.	verage values y, subject to th	e tolerances stipu	lated in NEMA		

Subject to change without notice

Three Phase Induction Motor - Squirrel Cage

Customer

:

Space heater information

Voltage: 110-127/200-240 V

Rev.		Changes Summary	Performed	Checked	Date			
Performed by								
Checked by				Page	Revision			
Date	22/01/2018			2/2				
This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.								

Subject to change without notice

