

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump NEMA Premium Efficiency Three-Phase
Product code : 13441210
Catalog # : 01536ET3H215JM-S

Frame	: 213/5JM	Locked rotor time	: 19s (cold) 11s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.6 A	Protection degree	: IP55
L. R. Amperes	: 112 A	Cooling method	: IC411 - TEFC
LRC	: 8.2x(Code J)	Mounting	: F-1
No load current	: 4.98 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3520 rpm	Noise level ²	: 70.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 22.1 ft.lb	Approx. weight ³	: 166 lb
Locked rotor torque	: 280 %		
Breakdown torque	: 330 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.6341 sq.ft.lb		
Design	: A		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	90.0	90.2	91.0	91.0	Max. traction	: 334 lb
Power Factor	0.49	0.76	0.85	0.89	Max. compression	: 499 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6209 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	22/01/2018			
			Revision	