DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Flameproof Motor NEMA Product code: 11360217 Premium Efficiency Three-Phase Catalog #: 00718XT3H213T Frame : 213T Locked rotor time : 21s (cold) 12s (hot) : 7.5 HP (5.5 kW) Output Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 575 V : 1000 m.a.s.l. Altitude Rated current : 7.53 A Protection degree : IP55 L. R. Amperes : 50.4 A Cooling method : IC411 - TEFC : 6.7x(Code H) LRC Mounting : F-1 No load current : 3.60 A Rotation¹ : Both (CW and CCW) Rated speed : 1765 rpm Noise level² : 58.0 dB(A) Starting method Slip : 1.94 % : Direct On Line Rated torque : 22.0 ft.lb Approx. weight³ : 167 lb Locked rotor torque : 240 % Breakdown torque : 280 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 1.38 sq.ft.lb Design : B 25% 50% 75% 100% Output Foundation loads 90.2 91.7 : 269 lb Efficiency (%) 87.0 88.5 Max. traction Power Factor 0.60 0.80 : 436 lb 0.37 0.73 Max. compression Drive end Non drive end 6207 2RS Bearing type 6308 2RS Sealing Oil Seal Lip Seal Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	24/01/2018			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_		
Customer		

Thermal protection

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	130 °C
2	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	24/01/2018			2/2	