

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663
Catalog # : 00136ET3E143T-W22

Frame : 143/5T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ² : 41.0 lb
Protection degree : IP55	Moment of inertia (J) : 0.0332 sq.ft.lb

Output [HP]	1	0.75	0.75	0.75	1	1	1
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	208-230/460	380	400	415	380	400	415
Rated current [A]	3.16-2.88/1.44	1.26	1.29	1.29	1.67	1.60	1.58
L. R. Amperes [A]	25.9-23.6/11.8	10.3	11.2	11.9	10.5	11.0	11.7
LRC [A]	8.2x(Code L)	8.2x(Code L)	8.7x(Code M)	9.2x(Code N)	6.3x(Code H)	6.9x(Code J)	7.4x(Code K)
No load current [A]	1.12-1.30/0.650	0.660	0.720	0.780	0.660	0.720	0.780
Rated speed [RPM]	3480	2900	2910	2920	2840	2865	2875
Slip [%]	3.33	3.33	3.00	2.67	5.33	4.50	4.17
Rated torque [ft.lb]	1.49	1.34	1.34	1.33	1.82	1.81	1.80
Locked rotor torque [%]	280	300	340	360	220	250	270
Breakdown torque [%]	340	340	380	420	250	280	310
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	39s (cold) 22s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level ²	68.0 dB(A)						
Efficiency (%)	25%						
	50%	75.0	72.9	72.3	71.7	77.0	77.0
	75%	79.0	77.6	77.6	77.6	78.5	78.5
	100%	81.5	78.9	79.0	79.2	78.5	78.5
Power Factor	25%						
	50%	0.63	0.66	0.59	0.55	0.74	0.67
	75%	0.74	0.77	0.70	0.67	0.84	0.78
	100%	0.80	0.84	0.78	0.75	0.87	0.84

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6205 ZZ	6204 ZZ	Max. traction : 28 lb
Sealing :	V'Ring	V'Ring	Max. compression : 69 lb
Lubrication interval :	-	-	
Lubricant amount :	-	-	
Lubricant type :	Mobil Polyrex EM		

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/01/2018			
			Page	Revision
			1 / 1	