

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM  
NEMA Premium Efficiency Three-Phase  
Product code : 12711992  
Catalog # : 00736ET3H213JM-W22

Frame	: 213/5JM	Locked rotor time	: 48s (cold) 27s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.01 A	Protection degree	: IP55
L. R. Amperes	: 50.5 A	Cooling method	: IC411 - TEFC
LRC	: 7.2x(Code H)	Mounting	: F-1
No load current	: 2.16 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3520 rpm	Noise level <sup>2</sup>	: 72.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 11.0 ft.lb	Approx. weight <sup>3</sup>	: 160 lb
Locked rotor torque	: 210 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.4665 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	87.2	87.5	89.5	89.5	Max. traction : 109 lb
Power Factor	0.52	0.75	0.84	0.88	Max. compression : 269 lb

	Drive end	Non drive end
Bearing type	: 6309 Z C3	: 6207 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: 19000 h	: 40000 h
Lubricant amount	: 13 g	: 0 g
Lubricant type	Mobil Polyrex EM	

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/01/2018			
		Page 1 / 1		Revision