

THIS IS AN UPDATED REVISION, THE
PREVIOUS ONE MUST BE DISREGARDED.

Grounding for leads 0.5–6 mm² / 20–10 AWG

NPT 1/2"

Main terminal box

Center hole
EM4 WEG TBG253
(DIN 332)

Technical drawing of a shaft-hub assembly. The shaft has a diameter of 4 mm and a length of 4 mm. The hub has an inner diameter of 8.5 mm and a length of 8.5 mm. The shaft is fitted into the hub with a fit of h9/j6. The keyway in the hub has a depth of 0.1 mm. The key is shown in cross-section with a width of 4 mm and a height of 1 mm. The shaft is shown in cross-section with a diameter of 4 mm. The hub is shown in cross-section with an inner diameter of 8.5 mm and an outer diameter of 11 mm. The key is shown in cross-section with a width of 4 mm and a height of 1 mm. The shaft is fitted into the hub with a fit of h9/j6. The keyway in the hub has a depth of 0.1 mm. The key is shown in cross-section with a width of 4 mm and a height of 1 mm. The shaft is shown in cross-section with a diameter of 4 mm. The hub is shown in cross-section with an inner diameter of 8.5 mm and an outer diameter of 11 mm.

DE Shaft End

Color RAL 7022										
Painting plan 207A										
Mounting B3L(E)										
ECM		LOC	SUMMARY OF MODIFICATIONS			EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	USERADMIN			THREE PH.MULTI M. H.EFF.MOTOR TRU METRIC						
CHECKED				FRAME 63 IP55 TEFC						
RELEASED				WEG code: 13982726						
REL DT	22.01.2018		WMO	Jaragua do Sul	Product Engineering	SHEET	1 / 1			

WEG's property. Forbidden reproduction without previous authorization