DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Product line : Rolled Steel JP Pump NEMA Product code: 13507660 Premium Efficiency Three-Phase Catalog #: 01018ET3E215JP-S Frame : 213/5JP Cooling method : IC411 - TEFC Insulation class Mounting : F-1 Duty cycle : Cont.(S1) Rotation¹ : Both (CW and CCW) Ambient temperature : -20°C to +40°C Starting method : Direct On Line Altitude : 1000 m.a.s.l. Approx. weight³ : 145 lb : IP55 Protection degree Moment of inertia (J) : 1.07 sq.ft.lb Design : B Output [HP] 10 7.5 7.5 Poles 4 4 Frequency [Hz] 60 50 50 Rated voltage [V] 208-230/460 190/380 220/415 Rated current [A] 27.0-24.4/12.2 22.4/11.2 20.6/10.9 L. R. Amperes [A] 189-171/85.4 170/85.1 179/94.8 LRC [A] 7.0x(Code H) 7.6x(Code J) 8.7x(Code L) No load current [A] 9.56-11.1/5.54 10.9/5.46 12.1/6.43 Rated speed [RPM] 1470 1760 1465 Slip [%] 2.22 2.33 2.00 Rated torque [ft.lb] 29.4 26.5 26.4 Locked rotor torque [%] 250 250 320 Breakdown torque [%] 300 320 390 Service factor 1.15 1.15 1.15 Temperature rise 80 K 80 K 80 K Locked rotor time 27s (cold) 15s (hot) 0s (cold) 0s (hot) 0s (cold) 0s (hot) Noise level² 60.0 dB(A) 57.0 dB(A) 57.0 dB(A) 25% 90.2 90.4 88.3 50% 91.0 90.1 88.7 Efficiency (%) 75% 90.7 90.2 91.0 100% 90.3 91.7 90.1 25% 0.32 0.41 0.38 50% 0.56 0.67 0.64 Power Factor 75% 0.76 0.78 0.69 0.78 100% 0.84 0.83 Drive end Non drive end Foundation loads Bearing type 6209 ZZ 6206 ZZ Max. traction : 517 lb Sealing V'Ring V'Ring Max. compression : 662 lb Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

()						
Rev.	Changes Summary		Perforr	Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	22/01/2018	1			1/1	