## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Cooling Tower High Efficiency Product code: 12172970 Three-Phase 00789EP3PCT254V2-W22 Catalog #: Frame : 254T Cooling method : IC411 - TEFC Insulation class Mounting : F-2 Duty cycle : Cont.(S1) Rotation<sup>1</sup> : Both (CW and CCW) Ambient temperature : -20°C to +40°C Starting method : Direct On Line : 1000 m.a.s.l. Approx. weight3 : 2.2 lb Altitude : IP55 : 2.62 sq.ft.lb Protection degree Moment of inertia (J) Output [HP] 1.75 7.5 Poles 4 8 60 Frequency [Hz] 60 Rated voltage [V] 200 200 Rated current [A] 22.4 10.6 L. R. Amperes [A] 144 39.1 LRC [A] 6.4x(Code H) 3.7x(Code J) No load current [A] 10.6 9.20 Rated speed [RPM] 1770 885 Slip [%] 1.67 1.67 Rated torque [ft.lb] 22.0 10.2 Locked rotor torque [%] 200 220 Breakdown torque [%] 280 280 Service factor 1.25 1.25 Temperature rise 80 K 80 K Locked rotor time 32s (cold) 18s (hot) 43s (cold) 24s (hot) Noise level<sup>2</sup> 64.0 dB(A) 54.0 dB(A) 25% 84.4 65.9 50% 85.5 66.0 Efficiency (%) 75% 87.5 75.0 100% 88.5 74.0 25% 0.39 0.16 50% 0.64 0.32 Power Factor 75% 0.75 0.40 100% 0.80 0.48 Non drive end Foundation loads Drive end 6209 Bearing type 6309 Max. traction : 136 lb 2RS C3 2RS C3 Sealing V'Ring V'Ring Max. compression : 138 lb Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	18/01/2018	1		1/2	

## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Three Phase induction violor - Squirer Cage								
Customer	:							
		Space heater informa	ntion					
Voltage: 110-127	7/200-240 V							
			T 5					
Rev.		Changes Summary	Performed	Checked	Date			
Performed by								
Checked by				Page	Revision			
Date	18/01/2018			2/2				