DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Cooling Tower High Efficiency Product code: Three-Phase Catalog #: 05089EP3HCT364V-W22 Frame : 364/5T Cooling method : IC411 - TEFC Insulation class Mounting : F-2 Duty cycle : Cont.(S1) Rotation¹ : Both (CW and CCW) Ambient temperature : -20°C to +40°C Starting method : Direct On Line : 1000 m.a.s.l. Approx. weight3 : 2.2 lb Altitude : IP55 : 19.9 sq.ft.lb Protection degree Moment of inertia (J) Output [HP] 12.5 50 Poles 4 8 Frequency [Hz] 60 60 Rated voltage [V] 575 575 Rated current [A] 47.8 17.1 L. R. Amperes [A] 421 75.3 LRC [A] 8.8x(Code K) 4.4x(Code G) No load current [A] 24.6 13.0 Rated speed [RPM] 1780 885 Slip [%] 1.11 1.67 Rated torque [ft.lb] 146 73.2 Locked rotor torque [%] 310 190 Breakdown torque [%] 350 229 Service factor 1.25 1.25 Temperature rise 80 K 80 K Locked rotor time 14s (cold) 8s (hot) 82s (cold) 46s (hot) Noise level² 70.0 dB(A) 60.0 dB(A) 25% 88.1 82.8 50% 89.5 84.0 Efficiency (%) 75% 91.0 87.5 100% 92.4 88.5 25% 0.39 0.21 50% 0.67 0.40 Power Factor 75% 0.78 0.52 100% 0.84 0.61 Non drive end Foundation loads Drive end Bearing type 6314 6314 Max. traction : 575 lb 2RS C3 2RS C3 Sealing WSeal WSeal Max. compression : 577 lb Lubrication interval Lubricant amount Lubricant type **POLYREA ESTER** OIL (WT/ENS)

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | | Changes Summary | Performed | Checked | Date |
|--------------|------------|-----------------|-----------|---------|----------|
| | | | | | |
| Performed by | | | | | |
| Checked by | | | | Page | Revision |
| Date | 18/01/2018 | | | 1/2 | |

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



| Three Phase induction wotor - Squirer Cage | | | | | | | | | | | |
|--|------------|----------------------|-----------|---------|----------|--|--|--|--|--|--|
| Customer : | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | Space heater informa | ntion | | | | | | | | |
| Voltage: 110-127/200-240 V | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | T 5 | | | | | | | | |
| Rev. | | Changes Summary | Performed | Checked | Date | | | | | | |
| Performed by | | | | | | | | | | | |
| Checked by | | | | Page | Revision | | | | | | |
| Date | 18/01/2018 | | | 2/2 | | | | | | | |