## DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:



## Customer

Product line		: W22 Cooling Tower High Efficiency Three-Phase		Product code :	12174046		
				Catalog # :	03089EP3Q W2	03089EP3QCT324VF1- W2	
Frame		: 324T		ng method	: IC411 - TE	FC	
Insulation class		: F Mount			: F-1		
Duty cycle		: Cont.(S1) Rotati			: Both (CW and CCW)		
Ambient temperature				ng method	: Direct On Line		
Altitude				x. weight <sup>3</sup>			
Protection degre	e	: IP55	Niome	ent of inertia (J)	•	)	
Output [HP] Poles		30			7.5		
Frequency [Hz]		60			60		
Rated voltage [V]		460			460		
Rated current [A]		37.2			14.2		
L. R. Amperes [A]		301		51.0			
LRC [A]		8.1x(Code J)			3.6x(Code F)		
No load current [A	1	17.0			8.80		
Rated speed [RPM]		17.0			885		
Slip [%]		1.11			1.67		
Rated torque [ft.lb]		87.3			43.9		
Locked rotor torque [%]		270			160		
Breakdown torque [%]		280			170		
Service factor		1.25			1.25		
Temperature rise		80 K			80 K		
Locked rotor time		19s (cold) 11s (hot)			90s (cold) 50s (hot)		
Noise level <sup>2</sup>		69.0 dB(A)	-		56.0 dB(A)		
Efficiency (%)	25%	89.4			81.0		
	50%	90.2			82.5		
	75%	91.0		84.0			
	100%	91.7			85.5		
Power Factor	25%	0.39		0.22			
	50%	0.64		0.38			
	75%	0.75	0.50				
	100%	0.81			0.57		
		Drive end Non drive end	I Found	Foundation loads			
Bearing type		: 6312 6212	Max. traction : 17 lb				
		2RS C3 2RS C3					
Sealing		: V'Ring V'Ring	Max. compression : 555 lb				
Lubrication interval							
Lubricant amount							
Lubricant type		: Mobil Polyrex EM					
Notes							
		ncel the previous one, which	These			th cinuccidal	
must be eliminated. (1) Looking the motor from the		e shaft end. MG-		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
	veight subjeo ocess.	olerance of +3dB(A). et to changes after					
Rev. Changes Summary				Performed	Checked	Date	
Performed by							
					-	<b>_</b>	
					Page	Revision	
Checked by	18/01/201				1/2		

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A. Subject to change without notice

Three Phase Induction Motor - Squirrel Cage

Customer

:

## Space heater information

Voltage: 110-127/200-240 V

Rev.		Changes Summary	Performed	Checked	Date		
Performed by							
Checked by				Page	Revision		
Date	18/01/2018			2/2			
This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.							

Subject to change without notice

