

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium
Efficiency Three-Phase

Product code : 12792770

Catalog # : 00158ET3H145T-SG

Frame : 143/5T
Output : 1.5 HP (1.1 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 1.62 A
L. R. Amperes : 13.3 A
LRC : 8.2x(Code K)
No load current : 0.867 A
Rated speed : 1750 rpm
Slip : 2.78 %
Rated torque : 4.44 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1101 sq.ft.lb
Design : B

Locked rotor time : 37s (cold) 21s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line

Output	25%	50%	75%	100%
Efficiency (%)	85.2	85.5	86.5	86.5
Power Factor	0.35	0.59	0.72	0.79

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision		
Checked by				
Date	22/01/2018			
		1 /		