

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM  
NEMA Premium Efficiency Three-Phase  
Product code : 13298533  
Catalog # : 00336ET3H145JM-W22

Frame	: 143/5JM	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.97 A	Protection degree	: IP55
L. R. Amperes	: 24.0 A	Cooling method	: IC411 - TEFC
LRC	: 8.1x(Code J)	Mounting	: F-1
No load current	: 1.04 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3460 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)
Slip	: 3.89 %	Starting method	: Direct On Line
Rated torque	: 4.49 ft.lb	Approx. weight <sup>3</sup>	: 56.9 lb
Locked rotor torque	: 330 %		
Breakdown torque	: 360 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0605 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	85.2	85.5	86.5	86.5	Max. traction : 114 lb
Power Factor	0.47	0.70	0.81	0.86	Max. compression : 171 lb

		Drive end	Non drive end
Bearing type	:	6206 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	22/01/2018			