

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA
Premium Efficiency Three-Phase

Product code : 11976535

Catalog # : 00158ET3ECT145T-W22

Frame	: 143/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-2
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ²	: 53.3 lb
Protection degree	: IP55	Moment of inertia (J)	: 0.1431 sq.ft.lb
Design	: B		

Output [HP]	1.5	1.5	1.5	1.5
Poles	4	4	4	4
Frequency [Hz]	60	50	50	50
Rated voltage [V]	208-230/460	380	400	415
Rated current [A]	4.36-4.04/2.02	2.42	2.33	2.30
L. R. Amperes [A]	36.6-33.9/17.0	15.5	16.3	17.0
LRC [A]	8.4x(Code L)	6.4x(Code H)	7.0x(Code J)	7.4x(Code K)
No load current [A]	1.81-2.10/1.05	1.05	1.15	1.20
Rated speed [RPM]	1755	1440	1445	1450
Slip [%]	2.50	4.00	3.67	3.33
Rated torque [ft.lb]	4.43	5.40	5.38	5.36
Locked rotor torque [%]	250	180	200	220
Breakdown torque [%]	340	240	280	300
Service factor	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)
Noise level ²	51.0 dB(A)	49.0 dB(A)	49.0 dB(A)	49.0 dB(A)
Efficiency (%)	25%			
	50%	82.5	82.5	81.0
	75%	85.5	84.0	84.0
	100%	86.5	84.1	84.1
Power Factor	25%			
	50%	0.60	0.67	0.60
	75%	0.70	0.76	0.70
	100%	0.79	0.82	0.79

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads	
Bearing type	: 6205 2RS	6204 2RS	Max. traction	: 115 lb
Sealing	: V'Ring	V'Ring	Max. compression	: 168 lb
Lubrication interval	: -	-		
Lubricant amount	: -	-		
Lubricant type	: Mobil Polyrex EM			

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/01/2018			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 2		Revision
Checked by					
Date	27/01/2018				