

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump High Efficiency Three-Phase

Product code : 13550880

Catalog # : 007180P3HFP213JPV-S

Frame : 213/5JP
 Output : 7.5 HP (5.5 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 575 V
 Rated current : 7.43 A
 L. R. Amperes : 48.3 A
 LRC : 6.5x(Code H)
 No load current : 3.46 A
 Rated speed : 1760 rpm
 Slip : 2.22 %
 Rated torque : 22.1 ft.lb
 Locked rotor torque : 200 %
 Breakdown torque : 260 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 0.8040 sq.ft.lb
 Design : B

Locked rotor time : 18s (cold) 10s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Cooling method : IC01 - ODP
 Mounting : W-6
 Rotation¹ : Both (CW and CCW)
 Noise level² : 59.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 109 lb

Output	25%	50%	75%	100%
Efficiency (%)	87.3	87.5	88.5	88.5
Power Factor	0.41	0.67	0.79	0.84

Efficiency (%)	87.3	87.5	88.5	88.5
Power Factor	0.41	0.67	0.79	0.84

Foundation loads

Max. traction : 274 lb
 Max. compression : 382 lb

	Drive end	Non drive end
Bearing type	6209 ZZ	6206 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	18/01/2018			
		Revision		