## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 Cooling Tower High Efficiency Product code: Three-Phase 04089EP3QCT326VF1-Catalog #: W2 Frame : 324/6T Cooling method : IC411 - TEFC Insulation class Mounting : F-1 Rotation<sup>1</sup> : Both (CW and CCW) Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Starting method : Direct On Line Approx. weight<sup>3</sup> Altitude : 1000 m.a.s.l. : 600 lb : 9.16 sq.ft.lb Protection degree : IP55 Moment of inertia (J) Output [HP] 40 10 Poles 8 4 Frequency [Hz] 60 60 Rated voltage [V] 460 460 Rated current [A] 47.9 18.0 L. R. Amperes [A] 335 55.8 LRC [A] 7.0x(Code H) 3.1x(Code D) No load current [A] 18.0 10.0 Rated speed [RPM] 1780 885 Slip [%] 1.11 1.67 Rated torque [ft.lb] 116 58.5 Locked rotor torque [%] 270 160 Breakdown torque [%] 280 170 Service factor 1.25 1.25 Temperature rise 80 K 80 K Locked rotor time 16s (cold) 9s (hot) 90s (cold) 50s (hot) 69.0 dB(A) 56.0 dB(A) Noise level<sup>2</sup> 25% 91.3 84.7 50% 91.5 85.0 Efficiency (%) 75% 92.4 87.0 100% 92.4 87.0 25% 0.45 0.26 50% 0.70 0.45 Power Factor 75% 0.80 0.56 100% 0.85 0.60 Non drive end Foundation loads Drive end Bearing type 6312 6212 Max. traction : 81 lb 2RS C3 2RS C3 Sealing V'Ring V'Ring Max. compression : 682 lb Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

• •					
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Data	18/01/2018			1/2	

## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Three Phase induction violor - Squirer Cage								
Customer	:							
		Space heater informa	ntion					
Voltage: 110-127	7/200-240 V							
			T 5					
Rev.		Changes Summary	Performed	Checked	Date			
Performed by								
Checked by				Page	Revision			
Date	18/01/2018			2/2				