

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JP
NEMA Premium Efficiency Three-Phase
Product code : 12712311
Catalog # : 07536ET3H365JP-W22

Frame	: 364/5JP	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 65.5 A	Protection degree	: IP55
L. R. Amperes	: 439 A	Cooling method	: IC411 - TEFC
LRC	: 6.7x(Code G)	Mounting	: F-1
No load current	: 17.6 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 79.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 109 ft.lb	Approx. weight ³	: 826 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 11.9 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	92.2	92.4	93.6	93.6	Max. traction : 573 lb
Power Factor	0.59	0.83	0.88	0.90	Max. compression : 1399 lb

	Drive end	Non drive end
Bearing type	: 6314 C3	6314 C3
Sealing	: Lip Seal	Lip Seal
Lubrication interval	: 4000 h	4000 h
Lubricant amount	: 27 g	27 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/01/2018			
		Page 1 / 1		Revision