

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :					
Product line : W22 Three-Phase		Product code : 12685553 Catalog # : 01009ES3EOW286T-W22			
Frame : 284/6T Output : 10 HP (7.5 kW) Poles : 8 Frequency : 60 Hz Rated voltage : 208-230/460 V Rated current : 30.3-27.4/13.7 A L. R. Amperes : 176-159/79.5 A LRC : 5.8x(Code H) No load current : 11.3-10.2/5.10 A Rated speed : 830 rpm Slip : 7.78 % Rated torque : 62.4 ft.lb Locked rotor torque : 310 % Breakdown torque : 0 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 6.12 sq.ft.lb Design : D		Locked rotor time : 36s (cold) 20s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : F-2 Rotation <sup>1</sup> : Both (CW and CCW) Noise level <sup>2</sup> : 54.0 dB(A) Starting method : Direct On Line Approx. weight <sup>3</sup> : 369 lb			
Output	50%	75%	100%	Foundation loads Max. traction : -184 lb Max. compression : 184 lb	
Efficiency (%)	82.5	84.0	82.5		
Power Factor	0.69	0.79	0.83		
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6311 C3	6211 C3		
Sealing	:	V'Ring	V'Ring		
Lubrication interval	:	20000 h	20000 h		
Lubricant amount	:	18 g	11 g		
Lubricant type	:	Mobil Polyrex EM			
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	19/01/2018			Page 1 / 1	Revision