

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 13273265  
Catalog # : 02512ET3H324T-W22G

|                       |                   |                             |                        |
|-----------------------|-------------------|-----------------------------|------------------------|
| Frame                 | : 324/6T          | Locked rotor time           | : 46s (cold) 26s (hot) |
| Output                | : 25 HP (18.5 kW) | Temperature rise            | : 80 K                 |
| Poles                 | : 6               | Duty cycle                  | : Cont.(S1)            |
| Frequency             | : 60 Hz           | Ambient temperature         | : -20°C to +40°C       |
| Rated voltage         | : 575 V           | Altitude                    | : 1000 m.a.s.l.        |
| Rated current         | : 24.3 A          | Protection degree           | : IP55                 |
| L. R. Amperes         | : 151 A           | Cooling method              | : IC411 - TEFC         |
| LRC                   | : 6.2x(Code G)    | Mounting                    | : F-1                  |
| No load current       | : 11.2 A          | Rotation <sup>1</sup>       | : Both (CW and CCW)    |
| Rated speed           | : 1180 rpm        | Noise level <sup>2</sup>    | : 62.0 dB(A)           |
| Slip                  | : 1.67 %          | Starting method             | : Direct On Line       |
| Rated torque          | : 110 ft.lb       | Approx. weight <sup>3</sup> | : 0.0 lb               |
| Locked rotor torque   | : 210 %           |                             |                        |
| Breakdown torque      | : 260 %           |                             |                        |
| Insulation class      | : F               |                             |                        |
| Service factor        | : 1.25            |                             |                        |
| Moment of inertia (J) | : 11.5 sq.ft.lb   |                             |                        |
| Design                | : B               |                             |                        |

|                |      |      |      |      |                  |           |
|----------------|------|------|------|------|------------------|-----------|
| Output         | 25%  | 50%  | 75%  | 100% | Foundation loads |           |
| Efficiency (%) | 91.5 | 91.7 | 93.0 | 93.0 | Max. traction    | : 1110 lb |
| Power Factor   | 0.40 | 0.65 | 0.77 | 0.82 | Max. compression | : 1110 lb |

|                      |   | Drive end        | Non drive end |
|----------------------|---|------------------|---------------|
| Bearing type         | : | 6312 C3          | 6212 C3       |
| Sealing              | : | V'Ring           | V'Ring        |
| Lubrication interval | : | 20000 h          | 20000 h       |
| Lubricant amount     | : | 21 g             | 13 g          |
| Lubricant type       | : | Mobil Polyrex EM |               |

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary | Performed              | Checked | Date |
|--------------|-----------------|------------------------|---------|------|
|              |                 |                        |         |      |
| Performed by |                 | Page Revision<br>1 / 1 |         |      |
| Checked by   |                 |                        |         |      |
| Date         | 19/01/2018      |                        |         |      |