

QTDC[™] SERIES



- 30% tighter housing than competitive models.
- Flangeless housing facilitates a seamless installation.
- Quiet fan operation at less than 0.7 sones at all CFM speeds.



QTDC[™] simplifies the way you work.

Energy Efficient Brushless Motor Design

At 1/3 the size of a standard fan motor, our new brushless DC motor:

- · Provides more room to move air more quietly.
- · Lasts longer than standard motors.
- · Weighs less to simplify overhead installation.

Twice the ENERGY STAR® Efficiency Standard

QTDC™ continues to save money long after installation. The brushless DC motor achieves 90% efficiency so you can feel good about letting it run while keeping the air more comfortable.

QTDC™ at a glance

- Choose fan or LED fan/light models with or without Sensaire[®] humidity sensing technology.
- Sensaire® Sense on Rise technology on fan model QTXE110150DCS and fan/light model QTXE110150DCSL.
- TrueSeal[™] damper technology creates an airtight seal from inside the housing.
- 6" round duct connector to reduce static pressure in ducting.
- UL Listed for use over bathtub or shower when connected to a GFCI protected branch circuit.
- Type IC, fits 2" x 8" and larger construction.

Flangeless housing simplifies installation.



Switch between 110, 130 or 150 CFM

You'll have fewer fans to inventory and the right size at installation. Switch the CFM to meet room requirements as well as ASHRAE 62.2 for spot and dwelling unit ventilation.



CFM

0.7

0.7

0.7

0.7

N/A









*THAN STANDARD FAN HOUSINGS

QTDC™ Specifications Sones at 130 Model Description Selectable CFM CFM CFM QTXE110150DC FAN 110-130-150 <0.3 0.4 QTXE110150DCF FAN FINISH PACK 110-130-150 < 0.3 0.4 QTXE110150DCL FAN WITH LED LIGHT 110-130-150 < 0.3 0.4 QTXE110150DCS HUMIDITY SENSING FAN 110-130-150 <N.3 0.4

HUMIDITY SENSING FAN WITH LED LIGHT



HOUSING PACK



110-130-150

110-130-150

<0.3

N/A

N/A

BROAN

Broan.ca

QTXE110150DCSL

QTXEDCH





