



# **Dry Type Distribution Ventilated Transformer**

T20P11F9916ESLS47

UPC:786680211829

#### **Dimensions:**

Height: 62.88 INLength: 33.97 INWidth: 29.97 IN

Weight:916 LB

**Notes:**Low sound design equivalent to 47 dB, NEMA TP-1 efficient

#### Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

#### **Specifications:**

• Special Features: Electrostatically shielded

Type: Dry type distribution, ventilated transformer

• Design: DS-3

Coil Material: Aluminum windings

• Enclosure: NEMA 2

• Frame: 821

• Frequency Rating: 60 Hz

• Phase: Single-phase

Primary Voltage: 240 x 480V
Secondary Voltage: 120/240V

• Tap Size: 1 at +5% FCAN, 2 at -5% FCBN x 2

at +2.5% FCAN, 4 at -2.5% FCBN

• Temperature Rating: 115°C

Volt Ampere Rating: 100 KVA
 Weathershield: WS13

• Wiring Connection: 261A



## **Supporting documents:**

• Eaton Specification Sheet - T20P11F9916ESLS47

### **Certifications:**

• UL Listed

Product compliance: No Data

\_\_\_\_\_

© 2016 Eaton. All rights reserved.