

pe.eaton.com

Class 1 Division 2 Groups C and D, Hazardous Location Transformer

Z48G22T45A

UPC:786680009440

Dimensions:

- Height: 26.58 IN
- Length: 12.76 IN
- Width: 25.15 IN

Weight:762 LB

Notes:Model A

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- Design: EPTZ
- Coil Material: Aluminum windings
- Enclosure: NEMA 3R
- Frame: 244H
- Frequency Rating: 60 Hz
- Phase: Three-phase
- Primary Voltage: 480∨
- Secondary Voltage: 240 delta/120 midtap
- Tap Size: 2 at -5% FCBN
- Temperature Rating: 115°C
- Volt Ampere Rating: 45 KVA
- Weathershield: Indoor-Outdoor
- Wiring Connection: 52A

Supporting documents:

• Eatons Volume 2-Commercial Distribution



• Eaton Specification Sheet - Z48G22T45A

Certifications:

• UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.