



Powering Business Worldwide

pe.eaton.com

DS7 Soft Start Controllers

DS7-340SX055N0-L

UPC:786685887272

Dimensions:

- **Height:** 5.47 IN
- **Length:** 6.34 IN
- **Width:** 3.66 IN

Weight:3.97 LB

Warranties:


- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Options:** Expanded temperature range down to -40°C
- **Amperage Rating:** 55A
- **Frame Size:** FR 3
- **Horsepower:** 40 hp
- **Number Of Poles:** Three-pole
- **Phase:** Three-phase
- **Protection:** IP20
- **Type:** Standard soft starter with internal bypass
- **Voltage Rating:** 480V
- **Wiring Connection:** Inline or Inside-the-Delta wiring configuration

Supporting documents:

- [DS7 Series soft start controller](#)
- [DS7 series soft start controllers, Frame 1 \(4-12A\)](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [Eaton Specification Sheet - DS7-340SX055N0-L](#)
- [Product Datasheet - DS7-340SX055N0-L](#)



Certifications: No Data

Product compliance: No Data

© 2016 Eaton. All rights reserved.