



Powering Business Worldwide

pe.eaton.com

DOE 2016 Efficient Transformer, Dry-type, Ventilated, Three- phase

B48M28T2216

UPC:786680147449

Dimensions:

- **Height:** 66.18 IN
- **Length:** 33.5 IN
- **Width:** 42.18 IN

Weight:2379 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Aluminum
- **Efficiency:** DOE 2016
- **Frame:** 945
- **Frequency Rating:** 60 Hz
- **Insulation:** 220C
- **Kva Rating:** 225 kVA
- **Material:** Al windings
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 208Y/120V
- **Sound Level:** NEMA ST20
- **Tap Size:** 2 at +2.5%, 4 at -2.5%
- **Temperature Rating:** 150°C rise
- **Weathershield:** WS62
- **Wiring Connection:** 283B

Supporting documents:

- [Eaton Specification Sheet - B48M28T2216](#)



Certifications:

- UL Listed

Product compliance:

- DOE2016 Efficient

© 2016 Eaton. All rights reserved.