

Eaton heavy duty DC disconnect

DCG2064FPM

UPC:786685624778

Dimensions:

- **Height:** 35.38 IN
- **Length:** 11.63 IN
- **Width:** 16.54 IN

Weight:45 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** DC disconnect/grounded system
- **Amperage Rating:** 200A
- **Application:** Solar
- **Enclosure:** NEMA 4
- **Enclosure Material:** Painted steel
- **Fuse Configuration:** Fusible
- **Ground:** Grounded
- **Main Lug Wire Size:** In/Out(LC): 300 MCM-#6, In/Out(SR): 300 MCM-#6
- **Maximum Voltage:** 600 Vdc
- **Number Of Circuits:** 2
- **Isolation:** Isolated return
- **Number Of Poles:** Two-pole
- **Series:** DC photovoltaic applications
- **Switch Type:** Single-throw, heavy duty safety
- **Switch Type 2:** DC photovoltaic systems
- **System Voltage:** 600 Vdc per pole

Supporting documents:

- [DC disconnects for grounded and ungrounded photovoltaic installations](#)

- [Eatons Volume 15-Solar Inverters and Electrical Balance of System](#)
- [Eaton Specification Sheet - DCG2064FPM](#)

Certifications:

- UL 98B
- NEC 690 per UL 1741

Product compliance: No Data