

## Global Brass Ball Valves

### Applications:

- for water and air only

### Features:

- pressure ratings:
  - 1/4" - 3/8" rated to **365 PSI**
  - 1/2" - 2" rated to **600 PSI**
- forged brass body
- maximum temperature: **248°F** (120°C)



### female NPT x female NPT

Size	Port	Brass	
		Part #	Price/E
1/4"	full	<b>FBVG25</b>	<b>\$7.50</b>
3/8"	full	<b>FBVG38</b>	<b>7.50</b>
1/2"	full	<b>FBVG50</b>	<b>11.80</b>
3/4"	full	<b>FBVG75</b>	<b>16.60</b>
1"	full	<b>FBVG100</b>	<b>27.25</b>
1 1/4"	full	<b>FBVG125</b>	<b>42.00</b>
1 1/2"	full	<b>FBVG150</b>	<b>59.00</b>
2"	full	<b>FBVG200</b>	<b>90.00</b>

## Solder End Brass Ball Valves

### Application:

- designed to provide the best protection against potential gas leakage under extreme duty or low pressure applications

### Features:

- pressure rating: **600 PSI** WOG; **150 PSI** working steam pressure
- maximum temperature: **366°F**
- brass body
- blow-out proof stem
- chrome-plated brass ball
- adjustable stem packing nut
- PTFE seat, seal, and thrust washer



Size	Port	Brass	
		Part #	Price/E
1/2"	full	<b>FBV50SE</b>	<b>\$23.95</b>
3/4"	full	<b>FBV75SE</b>	<b>32.65</b>
1"	full	<b>FBV100SE</b>	<b>48.15</b>
1 1/4"	full	<b>FBV125SE</b>	<b>86.80</b>
1 1/2"	full	<b>FBV150SE</b>	<b>125.55</b>
2"	full	<b>FBV200SE</b>	<b>178.15</b>

## Lead Free Brass Ball Valves

### Features:

- lead free refers to the wetted surface of pipes, fittings and fixtures in potable water systems that have a weighted average lead content = 0.25%. Source: California Health & Safety Code (116875). Vermont Act 193\*171NLF
- pressure rating: 600 WOG - 150 WSP
- maximum temperature: **366°F**
- PTFE seat and double O-ring stem packing

### female NPT x female NPT



Size	Port	Brass	
		Part #	Price/E
1/2"	full	<b>LFV50</b>	<b>\$26.75</b>
3/4"	full	<b>LFV75</b>	<b>38.00</b>
1"	full	<b>LFV100</b>	<b>57.00</b>
1 1/4"	full	<b>LFV125</b>	<b>99.00</b>
1 1/2"	full	<b>LFV150</b>	<b>146.00</b>
2"	full	<b>LFV200</b>	<b>214.00</b>