

King Crimp™ Style Global Cam and Groove



Only use the crimp style shanks with the crimp style sleeves and ferrules.


Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon™ products.

Type C Couplers

female coupler x hose shank

Features:

- All couplers are supplied with safety clips.
- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 78-79.



| Hose ID | A380 permanent mold aluminum | | ASTM C38000 forged brass | | 316 investment cast stainless | |
|---------|-------------------------------------|---------|----------------------------|---------|--------------------------------------|---------|
| | A380 Permanent Mold Aluminum Part # | Price | C38000 Forged Brass Part # | Price | 316 Investment Cast Stainless Part # | Price |
| 1" | G100-C-ALCR | \$14.05 | G100-C-BRCR | \$31.00 | G100-C-SSCR | \$36.60 |
| 1½" | G150-C-ALCR | 19.45 | G150-C-BRCR | 47.25 | G150-C-SSCR | 55.45 |
| 2" | G200-C-ALCR | 22.95 | G200-C-BRCR | 60.50 | G200-C-SSCR | 77.40 |
| 3" | G300-C-ALCR | 37.50 | G300-C-BRCR | 126.30 | G300-C-SSCR | 140.15 |
| 4" | G400-C-ALCR | 51.85 | G400-C-BRCR | 173.50 | G400-C-SSCR | 181.70 |
| 6" | G600-C-ALCR | 137.00 | --- | --- | G600-C-SSCR | 485.00 |

Type E Adapters

male adapter x hose shank



| Hose ID | A380 permanent mold aluminum | | ASTM C38000 forged brass | | 316 investment cast stainless | |
|---------|-------------------------------------|--------|----------------------------|---------|--------------------------------------|---------|
| | A380 Permanent Mold Aluminum Part # | Price | C38000 Forged Brass Part # | Price | 316 Investment Cast Stainless Part # | Price |
| 1" | G100-E-ALCR | \$7.55 | G100-E-BRCR | \$23.00 | G100-E-SSCR | \$28.40 |
| 1½" | G150-E-ALCR | 11.45 | G150-E-BRCR | 37.60 | G150-E-SSCR | 44.95 |
| 2" | G200-E-ALCR | 13.95 | G200-E-BRCR | 52.25 | G200-E-SSCR | 61.90 |
| 3" | G300-E-ALCR | 23.45 | G300-E-BRCR | 108.35 | G300-E-SSCR | 117.95 |
| 4" | G400-E-ALCR | 37.20 | G400-E-BRCR | 153.10 | G400-E-SSCR | 167.15 |
| 6" | G600-E-ALCR | 105.00 | --- | --- | G600-E-SSCR | 472.00 |



Pressure rating is based on the seal of the mating part. See ratings on page 32.