


Brass International Shore Connections



shore connection



shore connection 09-318





shore side

Features:

- meets US Coast Guard specifications for vessels 1000 gross tons or more
- makes possible the connection of two different threads between ship and shore or between ships
- 7" OD brass flange with 4¾" holes
- includes 8 washers, 4 hexagon brass nuts, 4 hex head bolts, 1 washer, 1 fiber gasket
- working pressure: 300 PSI
- standardly supplied with NST threads, also available in NPT and NYFD threads





ship side

Wharf Hydrants

Features:



- pentagon nut at top of spindle discourages unauthorized use
- hydrostatically tested
- maximum operating pressure: 300 PSI at 70°F (21°C)

| Inlet Female NPT | Outlet Male NST (NH) | Height Open | Height Closed | Cast Brass Part # | Price/E |
|---------------------|-------------------------|----------------|------------------|----------------------|----------|
| 3" | 2½" | 16.38 | 14.25 | WHYD3025F | \$932.15 |
| 4" | 2½" | 16.38 | 14.25 | WHYD4025F | 1053.70 |
| 4" | 4½" | 18.13 | 15.63 | WHYD4045F | 1310.00 |



hand wheel



pentagon hex nut

Replacement Parts

| Description | Part # | Price/E |
|------------------|--------------|---------|
| hand wheel | 46-030-00025 | \$26.00 |
| pentagon hex nut | 44-251-00006 | 16.20 |