


Domestic Ball Cone Check Valves

Application:

- For use with water, oil, air lines or inert gases. Not recommended for use on or near reciprocating pumps or other similar vibration causing machinery.

Features:

- tight shut-off with liquid media
- no radial alignment necessary
- straight through and streamlined for minimum change in velocity
- Reinforced PTFE check is spring loaded for fast seating action.
- pressure rating: **400 PSI** WOG, cold non-shock; **125 PSI** saturated steam
- cracking pressure: .5 PSI
- temperature range: **-20°F** to **353°F**



Pressure Ratings

Temperature	Pressure WOG (PSI)
-20°F to 100°F	400
200°F	200
250°F	160
275°F	150
300°F	140
325°F	130
353°F	125

female NPT x female NPT

Size	Brass		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
¼"	61-101	\$62.00	62-101	\$136.00
⅜"	61-102	62.00	62-102	136.00
½"	61-103	62.00	62-103	160.00
¾"	61-104	89.00	62-104	256.00
1"	61-105	120.00	62-105	350.00
1¼"	61-106	212.00	62-106	490.00
1½"	61-107	268.00	62-107	660.00
2"	61-108	440.00	62-108	1140.00
2½"	61-109	900.00	---	---
3"	61-100	1500.00	---	---



male NPT x female NPT

Size	Brass	
	Part #	Price/E
¼"	61-201	\$85.50
⅜"	61-202	85.50
½"	61-203	85.50
¾"	61-204	112.00
1"	61-205	162.00
1¼"	61-206	264.00
1½"	61-207	335.00
2"	61-208	560.00



800 PSI Stainless Steel Check Valve

Features:

- soft PTFE seat is spring loaded for fast seating action
- flow profile designed to minimize head loss
- temperature range **10°F** to **450°F**
- pressure rating: **800 PSI** WOG; **125 PSI** saturated steam
- cracking pressure: .5 PSI
- corrosion resistance, excellent for use on chemicals
- dual guided stem and disc

female NPT x female NPT

Size	316 Stainless Steel	
	Part #	Price/E
¼"	SSCVIL025	\$114.00
⅜"	SSCVIL038	114.00
½"	SSCVIL050	114.00
¾"	SSCVIL075	169.00
1"	SSCVIL100	200.00
1¼"	SSCVIL125	339.00
1½"	SSCVIL150	416.00
2"	SSCVIL200	472.00

