

## Hammer Unions 400 Series

**Features:**

- used on manifold and line connections, pump, suction and mud service
- up to **4,000 PSI NSCWP** (non-shock cold working pressure)
- red sub, black nut

Size	Configuration	NSCWP (PSI)	Forged Steel Part #	Price/E
2"	threaded	4000	<b>HU400200</b>	<b>\$148.00</b>
3"	threaded	4000	<b>HU400300</b>	<b>305.25</b>
4"	threaded	4000	<b>HU400400</b>	<b>387.45</b>



## 602 Series

**Features:**

- for use in mud, manifold service and truck mounting applications running water, oil or mud up to **6,000 PSI NSCWP** (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- orange sub, black nut

Size	Configuration	NSCWP (PSI)	Forged Steel Part #	Price/E
1"	threaded	6000	<b>HU602100</b>	<b>\$116.00</b>
2"	threaded	6000	<b>HU602200</b>	<b>269.20</b>
2"	butt weld	6000	<b>HU602200BW<sup>1</sup></b>	<b>234.85</b>
3"	threaded	6000	<b>HU602300</b>	<b>375.00</b>
3"	butt weld	6000	<b>HU602300BW<sup>1</sup></b>	<b>446.15</b>
4"	threaded	6000	<b>HU602400</b>	<b>550.00</b>
4"	butt weld	6000	<b>HU602400BW<sup>1</sup></b>	<b>704.50</b>

<sup>1</sup> butt weld ends are schedule 80



## 1002 Series

**Features:**

- for use in high pressure systems and truck mounting applications running water, oil or mud up to **10,000 PSI NSCWP** (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- blue sub, red nut

Size	Configuration	NSCWP (PSI)	Forged Steel Part #	Price/E
1"	threaded	10000	<b>HU1002100</b>	<b>\$223.15</b>
2"	threaded	10000	<b>HU1002200</b>	<b>293.40</b>
2"	butt weld	10000	<b>HU1002200BW<sup>1</sup></b>	<b>270.00</b>
3"	threaded	10000	<b>HU1002300</b>	<b>450.00</b>
3"	butt weld	10000	<b>HU1002300BW<sup>1</sup></b>	<b>610.55</b>
4"	threaded	10000	<b>HU1002400</b>	<b>758.20</b>
4"	butt weld	10000	<b>HU1002400BW<sup>1</sup></b>	<b>751.45</b>

<sup>1</sup> butt weld ends are schedule -XXS



## 1502 Series

**Features:**

- for use in extreme high pressure applications running water, oil or mud up to **15,000 PSI NSCWP** (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- red sub, blue nut

Size	Configuration	NSCWP (PSI)	Forged Steel Part #	Price/E
2"	threaded	15000	<b>HU1502200</b>	<b>\$303.85</b>
2"	butt weld	15000	<b>HU1502200BW<sup>1</sup></b>	<b>352.25</b>
3"	threaded	15000	<b>HU1502300</b>	<b>670.00</b>
3"	butt weld	15000	<b>HU1502300BW<sup>1</sup></b>	<b>730.30</b>
4"	threaded	15000	<b>HU1502400</b>	<b>1060.50</b>
4"	butt weld	15000	<b>HU1502400BW<sup>1</sup></b>	<b>1268.05</b>

<sup>1</sup> butt weld ends are schedule -XXS



R