

Cam and Groove Actuator Style Couplers

Applications:

- suited for vapor recovery, suction pump line and other applications where it is necessary to easily drain the hose or pipe for cleaning
- can also be used when product retention in a hose or pipe is desired and damage from accidental spill from an open coupler is not a concern
- couplers work with the DBA (Dry Break cam and groove) popped adapters on page 96 in applications where automatic closure for the coupler is not desired

Features:

- 316 stainless steel body
- 304 stainless steel internal components
- EZ Boss-Lock™ cam arms
- stainless steel locking lever standard
- available with Buna, FKM, FKM-B, EPDM, FPM, PTFE encapsulated silicone and PTFE encapsulated FKM seals
- use with standard cam and groove dust plugs sized one size larger than the dry disconnect size
- prevents spillage from normal and accidental disconnection of the connection
- replacement parts are available, contact Dixon™ for more information



Female NPT	Coupler Size	Seal Material	Stainless Steel	
			Part #	Price/E
1½"	2"	Buna	D2C71-150	\$1030.85
2"	2½"		D2C71-200	1135.10
1½"	2"	FKM	D2C72-150	1051.40
2"	2½"		D2C72-200	1156.90
1½"	2"	PTFE Encapsulated Silicone	D2C73-150	1272.75
2"	2½"		D2C73-200	1347.35
1½"	2"	EPDM	D2C74-150	1030.85
2"	2½"		D2C74-200	1135.10
1½"	2"	PTFE Encapsulated FKM	D2C77-150	1272.75
2"	2½"		D2C77-200	1347.35
1½"	2"	FKM-B	D2C79-150	1102.90
2"	2½"		D2C79-200	1214.60