Dixon™ Diesel and Gasoline Nozzles

FuelMaster™ Diesel Nozzles

Application:
- truck stops and terminal operations (not designed for use with gravity flow tanks, small 12 volt or AC utility pumps, farm or consumer pumps)

Features:
- high flow capacity
- Micro-touch valve provides smooth operation and exceptional flow control
- Roto-matic latch pin provides positive auto shut-off
- pure PTFE packing eliminates stem leaks
- super tough nylon hand guard
- easy to change 'locknut style' spout assembly
- green scuff guard

Optional Features:
- Underwriters Listed versions
- super tough nylon trigger hold-open clip
- 'no pressure, no flow' (NPNF) safety valve prevents the trigger from being held open if pressure is not present

Materials:
- body and spout: aluminum
- body caps: zinc
- seals: FKM
- poppet disk: FKM
- stem packing: PTFE
- hand-guard and trigger hold open clip: super tough nylon
- trigger: steel
- snap-on cover: plastic
- scuff guard: vinyl

Features:
- with trigger hold-open clip
- non Underwriters Listed nozzle

NPT Inlet	Spout Outlet	Weight (lbs)	Approximate Flow Rate at 20 PSI (GPM)	Part #	Price/E
1"	1-3/16"	3.5	35	***DFN100HF***	**$219.00**
1"	1-3/16"	3.6	45	***DFN100SF***	**304.00**



DFN100HF

Features:
- with trigger hold-open clip
  with 'no pressure, no flow' safety valve
- Underwriters Listed nozzle

NEW

NPT Inlet	Spout Outlet	Weight (lbs)	Approximate Flow Rate at 20 PSI (GPM)	Part #	Price/E
1"	1-3/16"	3.5	35	***DFN100HF-NPNF***	**$324.75**
1"	1-3/16"	3.6	45	***DFN100SF-NPNF***	**263.00**



DFN100SF

Features:
- without trigger hold-open clip
- Underwriters Listed nozzle

NEW

NPT Inlet	Spout Outlet	Weight (lbs)	Approximate Flow Rate at 20 PSI (GPM)	Part #	Price/E
1"	1-3/16"	3.5	35	***DFN100HF-NC***	**$224.00**
1"	1-3/16"	3.6	45	***DFN100SF-NC***	**308.00**

S