

King Crimp™ Style Ferrules



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon™ products.



Hose ID	Hose OD		Carbon Steel		304 Stainless Steel		Work. Pressure (PSI)		Ferrule ID	Ferrule Wall Thickness	Ferrule Overall Length
	From	To	Part #	Price	Part #	Price	cam & groove ¹	KC nipple ²			
3"	3-13/64"	3-16/64"	CF300-1CS	\$17.50	CF300-1SS	\$28.95	150	300	3.313"	.090"	4"
	3-17/64"	3-20/64"	CF300-2CS	17.50	CF300-2SS	28.95	150	300	3.375"	.090"	4"
	3-21/64"	3-24/64"	CF300-3CS	17.50	CF300-3SS	28.95	150	300	3.438"	.090"	4"
	3-25/64"	3-28/64"	CF300-4CS	17.50	CF300-4SS	28.95	150	300	3.500"	.090"	4"
	3-29/64"	3-32/64"	CF300-5CS	17.50	CF300-5SS	28.95	150	300	3.563"	.090"	4"
	3-33/64"	3-36/64"	CF300-6CS	17.50	CF300-6SS	28.95	150	300	3.625"	.090"	4"
	3-37/64"	3-40/64"	CF300-7CS	17.50	CF300-7SS	28.95	150	300	3.688"	.090"	4"
	3-41/64"	3-44/64"	CF300-8CS	17.50	CF300-8SS	28.95	150	300	3.750"	.090"	4"
	3-45/64"	3-48/64"	CF300-9CS	17.50	CF300-9SS	28.95	150	300	3.813"	.090"	4"
	3-49/64"	3-52/64"	CF300-10CS	17.50	CF300-10SS	28.95	150	300	3.875"	.090"	4"
	3-53/64"	3-56/64"	CF300-11CS	17.50	CF300-11SS	28.95	150	300	3.938"	.090"	4"
	3-57/64"	3-60/64"	CF300-12CS	17.50	CF300-12SS	28.95	150	300	4.000"	.090"	4"
	3-61/64"	4"	CF300-13CS	17.50	CF300-13SS	28.95	150	300	4.063"	.090"	4"
	4-1/64"	4-4/64"	CF300-14CS	17.50	CF300-14SS	28.95	150	300	4.125"	.090"	4"
	4-5/64"	4-8/64"	CF300-15CS	17.50	CF300-15SS	28.95	150	300	4.188"	.090"	4"
	4-9/64"	4-12/64"	CF300-16CS	17.50	CF300-16SS	28.95	150	300	4.250"	.090"	4"
4"	4-13/64"	4-16/64"	CF400-1CS	23.00	CF400-1SS	67.20	150	300	4.313"	.090"	4"
	4-17/64"	4-20/64"	CF400-2CS	23.00	CF400-2SS	67.20	150	300	4.375"	.090"	4"
	4-21/64"	4-24/64"	CF400-3CS	23.00	CF400-3SS	67.20	150	300	4.438"	.090"	4"
	4-25/64"	4-28/64"	CF400-4CS	23.00	CF400-4SS	67.20	150	300	4.500"	.090"	4"
	4-29/64"	4-32/64"	CF400-5CS	23.00	CF400-5SS	67.20	150	300	4.563"	.090"	4"
	4-33/64"	4-36/64"	CF400-6CS	23.00	CF400-6SS	67.20	150	300	4.625"	.090"	4"
	4-37/64"	4-40/64"	CF400-7CS	23.00	CF400-7SS	67.20	150	300	4.688"	.090"	4"
	4-41/64"	4-44/64"	CF400-8CS	23.00	CF400-8SS	67.20	150	300	4.750"	.090"	4"
	4-45/64"	4-48/64"	CF400-9CS	23.00	CF400-9SS	67.20	150	300	4.813"	.090"	4"
	4-49/64"	4-52/64"	CF400-10CS	23.00	CF400-10SS	67.20	150	300	4.875"	.090"	4"
	4-53/64"	4-56/64"	CF400-11CS	23.00	CF400-11SS	67.20	150	300	4.938"	.090"	4"
	4-57/64"	4-60/64"	CF400-12CS	23.00	CF400-12SS	67.20	150	300	5.000"	.090"	4"
	4-61/64"	5"	CF400-13CS	23.00	CF400-13SS	67.20	150	300	5.063"	.090"	4"
	5-1/64"	5-4/64"	CF400-14CS	23.00	CF400-14SS	67.20	150	300	5.125"	.090"	4"
	5-5/64"	5-8/64"	CF400-15CS	23.00	CF400-15SS	67.20	150	300	5.188"	.090"	4"
	5-9/64"	5-12/64"	CF400-16CS	23.00	CF400-16SS	67.20	150	300	5.250"	.090"	4"
6"	6-21/64"	6-28/64"	CF600-1CS	52.25	CF600-1SS	85.00	*	*	6.500"	.120"	5-7/8"
	6-29/64"	6-36/64"	CF600-2CS	52.25	CF600-2SS	85.00	*	*	6.625"	.120"	5-7/8"
	6-37/64"	6-44/64"	CF600-3CS	52.25	CF600-3SS	85.00	*	*	6.750"	.120"	5-7/8"
	6-45/64"	6-52/64"	CF600-4CS	52.25	CF600-4SS	85.00	*	*	6.875"	.120"	5-7/8"
	6-53/64"	6-60/64"	CF600-5CS	52.25	CF600-5SS	85.00	*	*	7.000"	.120"	5-7/8"
	6-61/64"	7-4/64"	CF600-6CS	52.25	CF600-6SS	85.00	*	*	7.125"	.120"	5-7/8"
	7-5/64"	7-12/64"	CF600-7CS	52.25	CF600-7SS	85.00	*	*	7.250"	.120"	5-7/8"
	7-13/64"	7-20/64"	CF600-8CS	52.25	CF600-8SS	85.00	*	*	7.375"	.120"	5-7/8"
	7-21/64"	7-28/64"	CF600-9CS	52.25	CF600-9SS	85.00	*	*	7.500"	.120"	5-7/8"

* consult Dixon™ for pressure rating

¹ based on using crimp cam and groove shanks

² based on using King™ combination nipples