

## Check Valves

### Features:

- Class 800
- ASTM A105, ANSI B120.1
- bolted bonnet
- pressure rating: **1975 PSI**
- maximum temperature: **800°F**
- can be used for steam service

Female NPT	Part #	Price/E
	<i>Forged Steel</i>	
1/2"	<b>FSCV50</b>	<b>\$128.40</b>
3/4"	<b>FSCV75</b>	<b>144.45</b>
1"	<b>FSCV100</b>	<b>202.60</b>
1 1/4"	<b>FSCV125</b>	<b>353.05</b>
1 1/2"	<b>FSCV150</b>	<b>375.10</b>
2"	<b>FSCV200</b>	<b>451.35</b>



## Spring-Loaded Check Valves

### Features:

- cracking pressure: 0.50 PSI
- NBR seat
- soft seat for bubble tight shutoff, spring loaded for fast seating action
- flow profile designed to minimize head loss
- pressure rating :1/2" - 2" **400 PSI WOG**; 3" - 4" **175 PSI WOG**
- temperature range: **10°F to 210°F** (-10°C to 100°C)

Female NPT	Part #	Price/E
	<i>Brass</i>	
1/2"	<b>CV050</b>	<b>\$18.60</b>
3/4"	<b>CV075</b>	<b>25.00</b>
1"	<b>CV100</b>	<b>34.00</b>
1 1/4"	<b>CV125</b>	<b>53.00</b>
1 1/2"	<b>CV150</b>	<b>79.30</b>
2"	<b>CV200</b>	<b>112.75</b>
3"	<b>CV300</b>	<b>355.90</b>
4"	<b>CV400</b>	<b>550.00</b>



## Strainer with Spring Loaded Check Valves

### Features:

- brass with NBR seat and stainless steel strainer
- soft seat for bubble tight shutoff, spring loaded for fast seating action
- flow profile designed to minimize head loss
- temperature range: **10°F to 210°F** (-10°C to 100°C)
- cracking pressure: **0.50 PSI**
- pressure rating: 1 1/2"-2" **400 PSI WOG**, 3"-4" **175 PSI WOG**

Female NPT	Part #	Price/E
1 1/2"	<b>BVFS20</b>	<b>\$89.60</b>
2"	<b>BVFS25</b>	<b>129.00</b>
3"	<b>BVFS35</b>	<b>379.50</b>
4"	<b>BVFS40</b>	<b>572.50</b>



Q