

Horizontal Swing Check Valves

Application:

- Swing check valves are designed to prevent back flow in plumbing and liquid piping systems, while offering full flow performance with a minimum of turbulence or pressure loss.

Features:

- brass disc
- for horizontal or vertical use
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.
- pressure rating: **200 PSI WOG**
- temperature range: **-20° to 150°F**




female NPT x female NPT

Size	Brass	
	Part #	Price/E
1/2"	SWCV50	\$19.90
3/4"	SWCV75	26.10
1"	SWCV100	35.55
1 1/4"	SWCV125	56.50
1 1/2"	SWCV150	71.10
2"	SWCV200	110.80
3"	SWCV300	309.80
4"	SWCV400	440.00

Domestic Swing Check Valves

Features:

- Class 150
- ASME B1.20.1
- metal seat
- 100% factory tested
- working pressure: **300 PSI cold, 150 PSI steam**
- temperature range: **-20°F to 406°F**



Female NPT	Brass	
	Part #	Price/E
1/2"	DSCV50	\$154.00
3/4"	DSCV75	187.00
1"	DSCV100	252.00
1 1/4"	DSCV125	333.00
1 1/2"	DSCV150	432.00
2"	DSCV200	646.00

Cast Iron Y Line Strainers

Features:

- cast iron body
- graphite gasket
- working pressure: **400 PSI WOG, 250 PSI steam**
- plug ported for blowdown service
- no replacement screens available

products used with the strainer:

- MNPT threaded close nipples, page 742
- brass ball valves, page 678
- MNPT threaded plugs, page 736



Female NPT	Description	Cast Iron	
		Part #	Price/E
1/4"	20 x 20 mesh	Y001	\$30.00
3/8"	20 x 20 mesh	Y002	30.00
1/2"	20 x 20 mesh	Y003	36.00
3/4"	20 x 20 mesh	Y004	44.00
1"	20 x 20 mesh	Y005	55.00
1 1/4"	20 x 20 mesh	Y006	78.00
1 1/2"	20 x 20 mesh	Y007	96.00
2"	20 x 20 mesh	Y008	144.00