


Synthetic Double Jacket Mill Hose

Application:

- ideal for open end discharge applications, not intended for fire fighting service 

Features:

- outer construction: double jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI at 70°F (21°C)**
- working pressure: **200 PSI at 70°F (21°C)**
- double jacket hoses are **not** recommended for use with field reattachable couplings 
- Consult Dixon® for pricing and availability of additional lengths and other configurations.

Uncoupled

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50UC
	1-13/16"	100'	DM15-100UC
2"	2-5/16"	50'	DM20-50UC
	2-5/16"	100'	DM20-100UC
2½"	2-7/8"	50'	DM25-50UC
	2-7/8"	100'	DM25-100UC



Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAF
	1-13/16"	100'	DM15100RAF
2½"	2-7/8"	50'	DM25-50RAF
	2-7/8"	100'	DM25100RAF



Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAS
	1-13/16"	100'	DM15100RAS
2"	2-5/16"	50'	DM20-50RAS
	2-5/16"	100'	DM20100RAS
2½"	2-7/8"	50'	DM25-50RAS
	2-7/8"	100'	DM25100RAS



Coupled with female and male NPT thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAT
	1-13/16"	100'	DM15100RAT
2"	2-5/16"	50'	DM20-50RAT
	2-5/16"	100'	DM20100RAT
2½"	2-7/8"	50'	DM25-50RAT



Coupled with female and male (C & E) global aluminum cam and groove, crimp sleeve

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50GAX
	1-13/16"	100'	DM15100GAX
2"	2-5/16"	50'	DM20-50GAX
	2-5/16"	100'	DM20100GAX

NEW

