NK-Series Japanese Pneumatic Couplings

Features:

- Japanese Industrial Interchange Pneumatic Coupling
- Interchanges with Nitto Kohki Hi-Cupla 200, Rectus Series 13, and CEJN Series 315
- Nitrile (Buna-N) seals are standard temperature range -40°F to 250°F (-40°C to 121°C)
- pressure rating: 300 PSI

Female Threaded Plugs

Body Size	Threads	Steel Part #
1⁄4"	1⁄4" - 18 NPT 1⁄4" -19 BSPP	NK2F2 NK2BF2

Male Threaded Plugs

Body Size	Threads	<i>Steel</i> Part #
1⁄4"	1⁄4" - 18 NPT 1⁄4" -19 BSPP	NK2M2 NK2BM2

Hose Barb Plug

	Body Size	Hose ID	<i>Steel</i> Part #
	1/4"	1/4"	NK2S2

Female Threaded Couplers

Body Size	Threads	<i>Steel</i> Part #
1/4"	1⁄4" - 18 NPT 1⁄4" -19 BSPP	2NKF2 2NKBF2

Male Threaded Couplers

Body Size	Threads	<i>Steel</i> Part #
1/4"	1⁄4" - 18 NPT 1⁄4" -19 BSPP	2NKM2 2NKBM2

Hose Barb Coupler



	Body Size	Hose ID	<i>Steel</i> Part #
1111	1/4"	1/4"	2NKS2