


Gaskets

- check gasket color code to be certain it is recommended for the service intended
- use lubricant on gasket
- for services not listed contact Dixon™ for recommendations



FKM

Size	FKM	
	Part #	Price/E
2"	G200V	\$38.35
3"	G300V	57.05
4"	G400V	79.45
6"	G600V	110.95
8"	G800V	188.50
10"	G1000V	233.95
12"	G1200V	295.55

Features:

- compound type: Fluoro Elastomer
- temperature range: **-13°F to 350°F**
- color code: black with blue stripe
- resistant to oxidizing acids, petroleum oils, hydraulic fluids, halogenated hydrocarbons and lubricants

EPDM

Size	EPDM	
	Part #	Price/E
1½"	G150E	\$34.60
2"	G200E	9.25
2½"	G250E	11.10
3"	G300E	12.30
4"	G400E	17.90
5"	G500E	65.75
6"	G600E	32.30
8"	G800E	52.60
10"	G1000E	67.00
12"	G1200E	92.00

Features:

- compound type: EPDM
- temperature range: **-22°F to 230°F**
- color code: black with green stripe
- for water, dilute acids, alkalis, salts, and many chemical services not involving hydrocarbons, oils, or gases.
- excellent oxidation resistance
- *Not for use with hydrocarbons*

Buna-N

Style	Black Buna with orange stripe		White Buna Gruvlok seal	
	Part #	Price/E	Part #	Price/E
1½"	G150T	\$34.60	---	---
2"	G200T	9.25	---	---
2½"	G250T	11.10	---	---
3"	G300T	12.30	---	---
4"	G400T	17.90	G400N	\$36.50
5"	G500T	65.75	---	---
6"	G600T	32.30	---	---
8"	G800T	52.60	---	---
10"	G1000T	67.00	---	---
12"	G1200T	92.00	---	---

Features:

- compound type: Buna-N
- temperature range: **-24°F to 176°F**
- for petroleum products, vegetable oils, mineral oils, and air contaminated with petroleum oils.
- *Not for use in hot water services*

Nuts and Bolts

Bolt Thread	Bolt Length	Torque Ft. Lbs.	Carbon Steel	
			Part #	Price/E
3/8"	2"	30	BLT38200	\$5.95
3/8"	2¼"	30	BLT38225	19.30
1/2"	2½"	50	BLT50212	5.95
1/2"	2¾"	50	BLT50234	8.15
1/2"	3"	50	BLT50300	9.80
5/8"	3¼"	75	BLT58314	5.35
3/4"	4¼"	75	BLT75414	17.50
7/8"	5"	200	BLT78500	18.50

Features:

- the nuts are a heavy hexagon design
- electroplated carbon steel
- The bolts are specifically designed for use with the couplings on pages 744-747.

Standards:

- conform to ASTM A183

R

Groove Lube

Features:

- water soluble
- non-toxic
- non-corrosive
- non-flammable
- NSF approved for use with potable water
- *Should not be used with HDPE pipe.*

Size	Container	Part #	Price/E
1 qt.	Tub	GROOVLUB32	\$263.00

