

Dixon® Frac Fittings

Male with Nut

Size	Figure	Part #
2"	206	<i>HUM206200CS</i> ¹ NEW
3"	100	<i>HUM100300CS</i>
	206	<i>HUM206300CS</i> ¹
4"	100	<i>HUM100400CS</i>
	206	<i>HUM206400CS</i> ¹
6"	100	<i>HUM100600CS</i>
	206	<i>HUM206600CS</i> ¹
8"	100	<i>HUM100800CS</i>
	206	<i>HUM206800CS</i> ¹

¹ includes nut and O-ring

3" and 4"



6" and 8"

Hose Coupling
Systems**Suction Service Fittings**

Size	Figure	Description	Forged Steel Part #
5"	50	socket weld x suction male hammer union (includes O-ring, no nut)	<i>HUSM500SW-1</i>
		socket weld x suction female hammer union	<i>HUSF500SW</i>
5"	N/A	split nut, suction and discharge, black	<i>HUS500RN</i>




HUSM500SW-1



HUSF500SW

Dixon® Frac Fitting O-rings

Size	Figure	Buna-N Part #
3"	206	<i>O238BU</i>
4"	206	<i>O347BU</i>
6"	206	<i>O440BU</i>
8"	206	<i>O447BU</i>

**King Crimp™ Style Short Frac Ferrules**

Hose ID	Hose OD		Ferrule Wall Thickness	Ferrule ID	Ferrule Overall Length	Carbon Steel Part #
	From	To				
	8-29/64"	8-36/64"	.120"	8.625"	4.25"	<i>CFS800-1CS</i>
	8-37/64"	8-44/64"	.120"	8.750"	4.25"	<i>CFS800-2CS</i>
	8-45/64"	8-52/64"	.120"	8.875"	4.25"	<i>CFS800-3CS</i>
	8-53/64"	8-60/64"	.120"	9.000"	4.25"	<i>CFS800-4CS</i>
	8-61/64"	9-4/64"	.120"	9.125"	4.25"	<i>CFS800-5CS</i>
	9-5/64"	9-12/64"	.120"	9.250"	4.25"	<i>CFS800-6CS</i>
	9-13/64"	9-20/64"	.120"	9.375"	4.25"	<i>CFS800-7CS</i>
	9-21/64"	9-28/64"	.120"	9.500"	4.25"	<i>CFS800-8CS</i>

